

Product Description

General	Full length steel bars firmly connects aluminum cassettes with spring	
	carpet wipers	
Aesthetic aspect	Spring carpet wipers with open construction	

Technical Specifications

Physical Properties

Physical Properties	4.40/00# (40	
Thickness	1-13/20" (42mm)	
Wiper surface	1.38" (35mm)	
Cassette profile material	Mill Finished Aluminum, grade 6063-T6	
Wiper strip material	Heavy duty, non fading, non shedding, odorless spring carpet	
Connector material	Steel / Aluminum bars	
Spacer material	Aluminum	
Space between 2 cassettes	0.19" (5mm)	
Format	Rigid	
Design	Open	
Mat module size	2' FB x 9.84' LR (610mm FB x 3000mm LR)	
Weight / Square Meter	32 lbs (14.5 kgs)	
Maximum rolling load / wheel,	1500 lbs.	
Recessed installation		
Frame options	Welcome mat-well frame of silver anodized aluminum,	
•	grade 6063-T6	

Component Color Options

Wiper strip Beige, Grey, Anthracite, Black (other colors available MOQ app	ied)
--	------

Product Properties

11 oddet 11 oper ties				
Performance	Standard	Result		
Critical Radiant Flux	ASTM E648	Class 1		
Coefficient of Friction	ASTM D2047	Meets or exceeds ADA guidelines		
Rolling Load	ASTM F2753	Able to sustain 1000 passes without damage		
Corrosion (Salt Spray)	ASTM B117	Able to sustain 100 hours of salt fog without any notable changes		

LEED

MR Credit 4	LEED-NC v.3	For 1-2 points: value of all materials = min. average 10% recycled content	40% pre-consumer and 46% post-consumer recycled
IEQ Credit 5	LEED-NC v.3	For 1 point: permanently installed entrance mats at least 10' long	Mat designed for permanent installation