


Features

- Surface mounted system designed for retrofit installation
- Easy to install and maintain
- Steel central flanges allows swift shift between positive and negative movements
- Specially designed spring assembly under the central plate provides silent passage to pedestrians and wheels
- Carpet / PVC floor coverings to be butt-joined with expansion joint frames for smooth movement over the system
- System allows full seismic movements
- System allows excellent shear movements
- Load rated subject to joint opening
- Vapor and Fire Barriers are optionally available

Straight Application DTS



DT
Series

EXT.
Application


INT.
Application

Seismic
Movement

FLOOR
USE

WALL
USE

Corner Application DTC



Details

Usage : Floor/Wall

Joint width : 2" - 8"

Optional : Vapor/Fire Barrier

Application	Code	JO	SH	SW	± Movement (%)			Load (Ton)
		Millimeter			Horizontal	Vertical	Shear	
Straight (S)	DTS 02	51	10	233	50	25	Excellent	9
	DTS 03	76	8	288	50	25	Excellent	9
	DTS 04	102	8	314	50	25	Excellent	9
	DTS 06	152	11	430	50	25	Excellent	6
	DTS 08	203	12	570	50	25	Excellent	6
Corner (C)	DTC 02	51	10	142	25	25	Excellent	9
	DTC 03	76	8	182	25	25	Excellent	9
	DTC 04	102	8	208	25	25	Excellent	9
	DTC 06	152	11	290	25	25	Excellent	6
	DTC 08	203	12	387	25	25	Excellent	6